

### Technické parametry CGR-01

DN [mm]	G	Max. průtok Q <sub>max</sub> [m <sup>3</sup> /h]	Min. průtok Q <sub>min</sub> [m <sup>3</sup> /h]							Verze					
			1:50	1:65	1:80	1:100	1:130	1:160	1:200						
40/50	16	25	0,5	0,4	0,3	0,25	0,2			p					
											w				
	25	40	0,8	0,6	0,5	0,4	0,3	0,25	0,2	s					
													w		
	40	65	1,3	1,0	0,8	0,6	0,5	0,4	0,3		s				
														w	
										p					
										w					
50	65	100	2,0	1,6	1,3	1,0	0,8	0,6	0,5	s					
															w
50/80	100	160	3,0	2,5	2,0	1,6	1,3	1,0	0,8	s					
80/100	100	160	3,0	2,5	2,0	1,6	1,3	1,0	0,8	p					
	160	250	5,0	4,0	3,0	2,5	2,0	1,6	1,3	s					
										w					
100	250	400	8,0	6,0	5,0	4,0	3,0	2,5	2,0	s					
	400	650	13	10	8,0	6,0	5,0	4,0	3,0	s					

*p* - základní, doporučený

*s* - vysokorychlostní verze, menší velikosti, možnost vyššího regulačního rozsahu, vyšší úroveň hluku

*w* - nízkorychlostní verze, větší velikosti, možnost nižšího regulačního rozsahu, nižší úroveň hluku